

Combination guide

4-1. AJ040TXJ2KG/EU

Cooling

Outdoor Unit	A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling at 35 °C/27 °C EER	Seasonal Efficiency (According to EN14825) Class	SEER	Qce kWh
			W		W			W			A						
			A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				
AJ040TXJ2KG 2 Unit	7	7	2,000	2,000	1,300	4,000	4,700	300	900	1,250	1.7	4.1	5.7	4.44	A+++	8.54	164
	7	9	1,780	2,220	1,300	4,000	4,700	350	920	1,270	1.9	4.2	5.8	4.35	A+++	8.51	165
	7	12	1,450	2,550	1,300	4,000	4,700	350	930	1,280	1.9	4.3	5.9	4.30	A+++	8.51	165
	9	9	2,000	2,000	1,300	4,000	4,700	350	940	1,290	1.9	4.3	5.9	4.26	A+++	8.51	165
	9	12	1,670	2,330	1,300	4,000	4,700	350	950	1,300	1.9	4.3	5.9	4.21	A+++	8.51	165

Heating

Outdoor Unit	A	B	Heating Capacity		Capacity		Power Consumption			Current			Effic. NOM. Heating at 7 °C/20 °C COP ¹	Seasonal Efficiency (According to EN14825) Class	SCOP	P design kW	Qhe kWh	
			W		W		W			A								
			A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD						MAX
AJ040TXJ2KG 2 Unit	7	7	2,100	2,100	1,000	4,200	4,700	280	900	1,180	1.4	4.1	5.4	4.67	A++	4.64	3.05	922
	7	9	1,840	2,360	1,000	4,200	4,700	280	920	1,190	1.4	4.2	5.4	4.57	A++	4.61	3.05	927
	7	12	1,550	2,650	1,000	4,200	4,700	280	930	1,200	1.4	4.3	5.5	4.52	A++	4.61	3.05	927
	9	9	2,100	2,100	1,000	4,200	4,700	280	940	1,210	1.4	4.3	5.5	4.47	A++	4.61	3.05	927
	9	12	1,800	2,400	1,000	4,200	4,700	280	950	1,220	1.4	4.3	5.6	4.42	A++	4.61	3.05	927

1. EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalogue.
2. The above is the value for connecting with the following indoor units. Wind-Free™ Elite: AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK.
3. You cannot connect a single unit.
4. Power consumption includes indoor unit power.

4-2. AJ050TXJ2KG/EU

Cooling

Outdoor Unit	A	B	Cooling Capacity		Capacity			Power Consumption			Current			Effic. NOM. Cooling at 35 °C/27 °C EER	Seasonal Efficiency (According to EN14825) Class	SEER	Qce kWh
			W		W			W			A						
			A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX				
AJ050TXJ2KG 2 Unit	7	7	2,000	2,000	1,300	4,000	4,700	350	980	1,290	1.9	4.5	5.9	4.08	A+++	8.51	165
	7	9	2,040	2,560	1,300	4,600	5,200	350	1,120	1,520	1.9	5.1	7.0	4.11	A+++	8.51	189
	7	12	1,820	3,180	1,400	5,000	5,500	350	1,230	1,510	1.9	5.6	6.9	4.07	A+++	8.51	206
	7	18	1,430	3,570	1,400	5,000	5,500	350	1,200	1,510	1.9	5.5	6.9	4.15	A+++	8.51	206
	9	9	2,500	2,500	1,400	5,000	5,500	350	1,220	1,500	1.9	5.6	6.9	4.10	A+++	8.54	205
	9	12	2,080	2,920	1,400	5,000	5,500	350	1,230	1,510	1.9	5.6	6.9	4.07	A+++	8.51	206
	9	18	1,670	3,330	1,400	5,000	5,500	350	1,230	1,510	1.9	5.5	6.9	4.15	A+++	8.51	206
	12	12	2,500	2,500	1,400	5,000	5,500	350	1,240	1,520	1.9	5.7	7.0	4.03	A+++	8.51	206
	12	18	2,060	2,940	1,400	5,000	5,500	350	1,240	1,520	1.9	5.6	7.0	4.15	A+++	8.51	206

Heating

Outdoor Unit	A	B	Heating Capacity		Capacity			Power Consumption			Current			Effic. NOM. Heating at 7 °C/20 °C COP ¹	Seasonal Efficiency (According to EN14825) Class	SCOP	Pdesign kW	Qhe kWh
			W		W			W			A							
			A	B	MIN	STD	MAX	MIN	STD	MAX	MIN	STD	MAX					
AJ040TXJ2KG 2 Unit	7	7	2,200	2,200	1,400	4,400	4,700	280	1,010	1,210	1.4	4.6	5.5	4.36	A++	4.61	3.05	927
	7	9	2,230	2,870	1,400	5,100	5,460	280	1,310	1,610	1.4	6	7.4	3.89	A++	4.61	4.21	1,277
	7	12	2,060	3,540	1,400	5,600	6,300	280	1,290	1,710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1,277
	7	18	1,530	4,170	1,400	5,600	6,300	280	1,270	1,70	1.4	5.7	7.8	4.41	A++	4.61	4.07	1,237
	9	9	2,800	2,800	1,400	5,600	6,300	280	1,280	1,700	1.4	5.9	7.8	4.38	A++	4.64	4.21	1,270
	9	12	2,400	3,200	1,400	5,600	6,300	280	1,290	1,710	1.4	5.9	7.8	4.34	A++	4.61	4.21	1,277
	9	18	2,020	3,680	1,400	5,600	6,300	280	1,270	1,70	1.4	5.7	7.8	4.41	A++	4.61	4.07	1,237
	12	12	2,800	2,800	1,400	5,600	6,300	280	1,300	1,720	1.4	5.9	7.9	4.31	A++	4.61	4.21	1,277
	12	18	2,280	3,420	1,400	5,600	6,300	280	1,280	1,720	1.4	5.8	7.9	4.38	A++	4.61	4.07	1,237

1. EER and COP declared only for the purpose of tax deductions in force at the time of the creation of this catalogue.
2. The above is the value for connecting with the following indoor units. Wind Free™ Elite: AR07TXCAAWK, AR09TXCAAWK, AR12TXCAAWK.
3. You cannot connect a single unit.
4. Power consumption includes indoor unit power.