

# Specifications

## MSP Duct (drain pump included)

- High efficiency microchannel heat exchanger.
- Built-in electronic expansion valve (EEV) for refrigerant flow control (2000-step).
- Auto Restart function.
- Condensation drain pump.
- Long-life HD 40 permanent filter is included.
- Auto ESP function.
- SPi Ioniser.



Indoor Unit		AJ052TNMDEG/EU	
<b>Capacity</b>			
	Cooling	kW	5.2
	Heating up to +7 °C	kW	5.6
<b>Performance</b>			
Airflow Rate		m <sup>3</sup> /min	16.3/15.0/13.5
Sound Power	Cooling	dB(A)	59
Sound Pressure	H/M/L	dB(A)	42/41/39
<b>Electrical Data</b>			
Power Source		Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz
Power Consumption	Cooling	W	170
	Heating	W	170
Current Input	Cooling	A	1.04
	Heating	A	1.04
<b>Dimensions</b>			
Net Dimensions (W x H x D)		mm	900 x 260 x 480
Net Weight		kg	28.3
<b>Refrigerant</b>			
Piping Connections	Liquid Pipe	ø, inch	1/4
	Gas Pipe	ø, inch	1/2
Piping Connections	Drain Pipe	ø, mm	VP25 (OD 32, ID 25)
<b>Others</b>			
Accessories	Drain Pump		MDP-M0755GU3
	Max. Lifting Height/ Displacement	mm / litres/h	750/24
	Air Filter		Removable/Washable

### Accessories



Advanced Wired Controller	Simple Type Controller	Touch Controller	Wired Remote Controller	Wi-Fi Kit
MWR-WG00JN/MWR-WG00KN	MWR-SH00N	MWR-SH11N	MWR-WE13N	MIM-H04EN